Candle

24V DC

M09501.000.0410





Data sheet


CODE	M09501.000.0410
SYSTEM POWER CONSUMPTION	2,8W
EFFICACY	119lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	286lm
LUMEN OUTPUT	238lm
EFFICIENCY	83.2%
WEIGHT	0,37 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 65,0 x 13,0 cm













Turned aluminium heat sink.

Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270

Diffuser in partially mat borosilicate glass tube.

³m (118,1") long suspension and power cable in transparent PVC.

Provided without power canopy, complete with cable clamp on the cable's free $\,$ extremity.

Candle

Accessories / power supply

XM100/24 DIM C € [HI] X (m)	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	
XM18/24 DIM CEERL M	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	175 mm 0 45-7
XM35/24 DIM C € [HL] X (m)	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	25 Em 27 118 mm 4 2/5*
XM60/24 DIM C € EHL X (iii)	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	
YDV.024.030.A01	LED driver, 30W 24V DC.	\$ 20 20 20 20 20 20 20 2
YDV.024.060.A01	LED driver, 60W 24V DC.	1/2 1/2
YDV.024.120.A01	LED driver, 120W 24V DC.	\$\\\ \begin{align*} \

Candle

Accessories / power supply and fixing

XM8901-03 LED	Canopy for power supply and suspension up to 3 24V DC constant voltage models maximum.	3.5. 13/8,*
CE EHI 🗵 🐽		3, 27
		42 16 ⁵ /9"
		10 49
XM8901-05 LED	Canopy for power supply and suspension up to 5 24V DC constant voltage models maximum.	3.55
CE EHI 🗵 🐽		76 80°
XM8901-06 LED	Canopy for power supply and suspension up to 6 24V DC constant voltage models maximum.	3.55 - 1.35 - 1.55
CE FHI 🗷 🐽		10.
		42
		16 %"
XM8901-09	Canopy for power supply with 9 outputs.	3.8
CE EHI 🗵 🐽		45
		72,5 28 4/1"
XM8901-15	Canopy for power supply with 15 outputs.	3.88
C € EHI <u>X</u> ŵ		45
		72,5
		28 4/7
XM9001-03	Canopy for power supply with 3 outputs.	9.0
CE EHI 🗵 👊		15 4/7*
XM9001-07	Canopy for power supply with 7 outputs.	3.9
CE FAI Z m		
		399.5
XM9001-12	Canopy for power supply with 12 outputs.	3.9
CE IHI X		
		70 V
XM9001-21	Canopy for power supply with 21 outputs.	
CE EHL X (m)		
		10.

Candle

Accessories / power supply and fixing

XM9201-01

Recessed canopy for electric cable suspensions. Suitable for 24V fixtures: remote driver 24V needed.



