PANZERI

To-be

220-240V AC ON-OFF

L02617.065.0501





Data sheet

CODE	L02617.065.0501
SYSTEM POWER CONSUMPTION	7W
EFFICACY	51.86lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	546lm
LUMEN OUTPUT	363lm
EFFICIENCY	66.5%
WEIGHT	0,74 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	5,0 x 105,0 x 10,0 cm



Suspension lighting fixture for interiors, with direct light emission.

 ${\sf Extruded\ aluminium\ structure\ in\ white,\ mat\ black,\ bronze\ or\ mat\ brass\ polyacrylic\ paint}$ or with gold leaf coating.

Extruded aluminium heat sink.

Modelled polycarbonate diffuser with opaline finish.

Turned brass end cap in polyacrylic paint.

 $2m\,(78,\!7")$ long suspension and power cable in transparent PVC.


Power canopy with pickled sheet metal ceiling bracket and extruded aluminium $\,$ covering in white, mat black, bronze or mat brass polyacrylic paint or with gold leaf coating.







Technical drawing



Polar diagram

