



807002 - 807005

RING POLE MEDIUM

Floodlight for outdoor installation on a pole diam. 60 mm or 76 mm, with 355° swivel pole attachment and allowing horizontal adjustment of +90° / -40°. Phosphochromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets and o-rings, with screws in stainless steel. Swivel pole joint with graduated scale and mechanical aiming lock. Built-in LED driver, with 1 COB CREE "CXB 1512" LED. IP66 rating.

807002








807005







Technical features















Technical data

IP Rating	IP66
IK Rating	IK10
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M16 rubber grommet
Power cable	Not included





807002	SINGLE RING POLE MEDIUM - 16 WATT 220-240V 50-60HZ		
light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	14°	1.900	118.75
cob led	35°	1.813	113.31
cob led	55°	1.722	107.62
4000°K neutral-white			
cob led	14°	2.000	125.00
cob led	35°	1.900	118.75
cob led	55°	1.805	112.81

Technical data	
Wattage	16 WATT
ight source	1 COB CREE "CXB 1512" LED
Gross weight	3,00 Kg
Gross weight	3,00 Kg



Colors options

Textured Grey RAL 9006 Anthracite Grey RAL 7016 Matt Black (on request)

807005	DOUBLE RING POLE MEDIUM - 2X16 WATT 220-240V 50-60HZ			
light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
3000°K warm-white				
cob led	14°	2 x 1.900	118.75	
cob led	35°	2 x 1.813	113.31	
cob led	55°	2 x 1.722	107.62	
4000°K neutral-white				
cob led	14°	2 x 2.000	125.00	
cob led	35°	2 x 1.900	118.75	
cob led	55°	2 x 1.805	112.81	
	· · · · · · · · · · · · · · · · · · ·	<u> </u>		

Technical data		
Wattage	2X16 WATT	
Light source	2 COB CREE "CXB 1512" LED	
Gross weight	5,50 Kg	



Colors options

Textured Grey RAL 9006 Anthracite Grey RAL 7016 Matt Black (on request)

POLES & ACCESSORIES

Full technical details of poles and accessories for poles are available at the end of the catalogue

BURIED POLES		
code	h. mm.	
809901	3.500	
809902	4.500	
809903	5.500	
809909	TOP CAP DIAM 76mm	

POLES WITH BASE-PLATE	
code	h. mm.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809909	TOP CAP DIAM 76mm

