

# BASIC SQUARE




## MINIMO INGOMBRO ED ATTENZIONE AL BUDGET.

In Basic Square, incasso a scomparsa totale da interni in Coral® per installazione a soffitto di cartongesso o laterizio, le linee geometriche e il design minimale si compongono per creare una luce concreta, che mostra fin dal primo sguardo tutta la sua consistenza. Un apparecchio da interni adatto ad accogliere unicamente sorgenti luminose LED, retrocesse di 20 mm rispetto al filo del soffitto.

## MINIMUM DIMENSIONS AND ATTENTION TO THE BUDGET.

*In Basic Square, an indoor totally disappearing recessed luminaire made of Coral®, installable on plasterboard or brick ceilings, geometrical lines and minimal design come together to create a concrete light, that shows all its consistency since the first glance. Designed for the indoor, it can be only provided with LED luminescent sources positioned 20 mm backwards from the ceiling level.*



## TECHNICAL FEATURES

Code	3111.00	3112.00	3113.Z.00
Type	Downlight 90°	Downlight 90°	Downlight 90°
Material	00: Coral®	00: Coral®	00: Coral®
Weight	0.7 Kg	0.7 Kg	0.8 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20	IP20
Insulation class	III	I	III
Control gear	Electronic transformer (not included)	-	Constant current electronic driver (not included)
Dimensions	A: 70 mm; B: 90 mm	A: 80 mm; B: 100 mm	A: 80 mm; B: 100 mm
Cut out for plasterboard	150 x 150 mm	150 x 150 mm	150 x 150 mm
Lamp type	QR CB 51 LED (optional)	QPAR 16 LED (optional)	LED 500 mA Vf: 18 VDC
Lamp wattage	-	-	1 x 9W
Luminous efficacy	-	-	1125 lm - 3000K
Light distribution	-	-	Wide beam 40°
Fitting	GU5.3	GU10	-
Light colour	-	-	White 3000K White 2700K I 4000K (on request)
Light hole	50 x 50 mm	50 x 50 mm	50 x 50 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz	By driver (optional)
CRI	-	-	>90
Emergency	-	-	-
Energy efficiency class	A	A	A++
Note	-	-	On request available dimmable PUSH or DALI.

## OPTIONAL ACCESSORIES

product code	optional code	description	info
3111.00	H8060.LED	Dimmable electronic transformer	<b>Max watt 60W Volts · Hz 230/12V · 50/60Hz</b>
	0008KIT	Kit LED dimmable	<b>Bulb 7W · 12V</b>
	BR3111LT	Brick box	<b>Dimensions L: 195 mm; W: 150 mm; D: 160 mm (instructions on page 502)</b>
3112.00	0009KIT	Kit LED dimmable	<b>Bulb 6W · 220-240V</b>
	BR3112LT	Brick box	<b>Dimensions L: 195 mm; W: 150 mm; D: 160 mm (instructions on page 502)</b>
3113.Z.00	H8500.E	Constant current electronic driver. Remote installation	Suitable for n°2 code 3113.Z.00 - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 3113.Z.00 - 500 mA
	BR3113LT	Brick box	<b>Dimensions L: 195 mm; W: 150 mm; D: 160 mm (instructions on page 502)</b>

