PANZERI

Bella


220-240V AC dimmable (Step DIM)


Data sheet

CODEC05202.011.0509SYSTEM POWER CONSUMPTION5WEFFICACY77.6lm/WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460ImLIMEN OUTPUT388ImEFFICIENCY0.88 KgWEIGHT0.88 Kg		
EFFICACY77.6lm/WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460ImLUMEN OUTPUT388ImEFFICIENCY0,88 Kg	CODE	C05202.011.0509
LIGHT SOURCELEDLIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460ImLUMEN OUTPUT388ImEFFICIENCY84.3%WEIGHT0,88 Kg	SYSTEM POWER CONSUMPTION	5W
LIGHT SOURCE LIFETIMEL80 (B10) 70.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460lmLUMEN OUTPUT388lmEFFICIENCY64.3%WEIGHT0,88 Kg	EFFICACY	77.6lm/W
COLOUR TEMPERATURE 2700K Ra>90 LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,88 Kg	LIGHT SOURCE	LED
LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX460lmLUMEN OUTPUT388lmEFFICIENCY84.3%WEIGHT0,88 Kg	LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,88 Kg	COLOUR TEMPERATURE	2700K Ra>90
FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,88 Kg	LIGHT DISTRIBUTION	adjustable
ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,88 Kg	POWER SUPPLY	220-240V AC
DRIVER integrated included NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,88 Kg	FREQUENCY	50/60Hz
NOMINAL LUMINOUS FLUX 460lm LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,88 Kg	ELECTRICAL CONFIGURATION	dimmable (Step DIM)
LUMEN OUTPUT 388lm EFFICIENCY 84.3% WEIGHT 0,88 Kg	DRIVER	integrated included
EFFICIENCY 84.3% WEIGHT 0,88 Kg	NOMINAL LUMINOUS FLUX	460lm
WEIGHT 0,88 Kg	LUMEN OUTPUT	388lm
	EFFICIENCY	84.3%
	WEIGHT	0,88 Kg
PROTECTION DEGREE IP20	PROTECTION DEGREE	IP20
COLOUR TOLLERANCES SDCM 3	COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS 17,0 x 40,0 x 16,0 cm	PACKING DIMENSIONS	17,0 x 40,0 x 16,0 cm



Technical drawing














Table lighting fixture for interiors, with swivelling light beam. Pickled sheet metal bearing base in polyacrylic paint. Body in tapered steel tube in white, black, bronze, mat brass or titanium polyacrylic paint. Turned brass joint in polyacrylic paint.

Die-cast aluminium structure in polyacrylic paint.

Die-cast aluminium swivelling head in polyacrylic paint.

Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.

Push-button to adjust luminosity according to 5 levels of visual comfort. Equipped with a 1,4m (55,1") long power cable with jack connector and adapter plug.

Polar diagram

